

Grounding Bushings

Description:

Procoat grounding bushings are used on threaded PVC-coated rigid conduit to provide a means of grounding conduit through an insulated bushing.

Features:

- 40 mil gray PVC exterior coating
- 2 mil gray urethane interior coating
- 10 trade sizes from 1/2" through 4"
- Aluminum lug for copper or aluminum grounding conductor



GROUNDING BUSHINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2" | RGB15MP | 0.1 |
| 3/4" | RGB20MP | 0.1 |
| 1" | RGB25MP | 0.1 |
| 1-1/4" | RGB32MP | 0.2 |
| 1-1/2" | RGB40MP | 0.2 |
| 2" | RGB50MP | 0.3 |
| 2-1/2" | RGB65MP | 0.5 |
| 3" | RGB80MP | 0.7 |
| 3-1/2" | RGB90MP | 1.0 |
| 4" | RGB100MP | 1.1 |

Split Couplings

Description:

Procoat split couplings are used to connect two pieces of conduit where the conduit can't be turned because of limited clearance between runs or a wall or other obstruction.

Features:

- 40 mil gray PVC exterior coating
- 2 mil gray urethane interior coating
- 12 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings



SPLIT COUPLINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2" | SPC15P | 0.2 |
| 3/4" | SPC20P | 0.3 |
| 1" | SPC25P | 0.4 |
| 1-1/4" | SPC32P | 0.6 |
| 1-1/2" | SPC40P | 0.7 |
| 2" | SPC50P | 1.0 |
| 2-1/2" | SPC65P | 2.3 |
| 3" | SPC80P | 3.0 |
| 3-1/2" | SPC90P | 3.8 |
| 4" | SPC100P | 4.1 |
| 5" | SPC125P | 6.0 |
| 6" | SPC150P | 8.6 |